



## Declaration of Performance (DoP)

No. F 500-CPR-130830	
<b>Product Type:</b>	Roomheaters fired by solid fuel
<b>Type, batch or serial number:</b>	<b>Jøtul F 500</b>
<b>Intended use of the product:</b>	Roomheater burning solid fuel without water supply
<b>Name and Address of the manufacturer:</b>	Jøtul AS Postboks 1411, 1602 Fredrikstad, Norway Tel.: +47 69 35 90 00 E-mail: post@jotul.no
<b>AVCP:</b> <i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i>	System 3
<b>Notified body:</b>  NB-No: Test report no:	Rhein-Ruhr Feuerstätten Prüfstelle / SP Swedish National Testing Institute 1625 / 0402 RRF-40 06 1186 / P4 00842-B
<b>Declared performance:</b>	
Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety Reaction to fire Distance to combustible materials	A1 Minimum distances, in mm Distance with heatshield at the back (*) Rear = 600 (*100) Sides = 400 Corner = 500 (*300) Front = NPD <i>See also the installation instructions</i>
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,10 %] NOx [56 mg/m <sup>3</sup> ] OGC [51 mgC/m <sup>3</sup> ] PM [57 mg/m <sup>3</sup> ]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T [285°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output Normal heat output Room heating output Water heating output	8,5 kW - kW -*kW
Energy efficiency	η [78%]

**Declaration:**

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager


---

*(Name and function)*

Fredrikstad, August 30th, 2013

---

*(Place and date of issue)*

  
*(Signature)*