

# DECLARATION OF PERFORMANCE

SalzMII-CPR-2020/06/08-GB



## PRODUCT

<b>Product type</b>	Slow heat release appliance
<b>Type designation</b>	Salzburg M II
<b>Product identification</b>	See product instruction manual
<b>Intended area of use</b>	Heating of rooms in residential buildings
<b>Fuel</b>	Wood

## MANUFACTURER

<b>Name</b>	Nordpeis AS
<b>Address</b>	Gjellebekkstubben 11 3420 Lierskogen, Norway

## CHECKS

<b>According to AVCP Standard</b>	System 3 EN 15250:2007
<b>Test institute</b>	Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625 has checked declared performance and issued test report no. RRF - 50 20 5549, RRF - 50 11 2758

## DECLARED PERFORMANCE

Essential Characteristic	Performance	Harmonized technical specification
Reaction to fire	A1	EN 15250:2007
Minimum distances to combustible material	50/150 mm rear 100 mm side other safety distances according product manual	
Risk of falling embers	Approved	
Emission from combustion:		
Carbon monoxide at 13% O <sub>2</sub>	CO = 1188 mg / m <sup>3</sup>	
Oxygen nitride NOx at 13% O <sub>2</sub>	NOx = 142 mg / m <sup>3</sup>	
Organic Gaseous Carbon at 13% O <sub>2</sub>	OGC = 81 mg / m <sup>3</sup>	
Particulate Matter at 13 O <sub>2</sub>	PM = 32 mg / m <sup>3</sup>	
Surface temperatures	Approved	
Cleanability	Approved	
Mechanical durability	Approved	
Releases of Hazardous Substances	Approved	
Total thermal output	39,4 kWh	
Nominal output after elapsed time at 25% of max. mean temp.	P = 2,4 kW	
Flue gas temperature at nominal output	t <sub>a</sub> = 157 °C	
Energy efficiency	η = 84 %	

The undersigned is responsible for the manufacture and conformity with declared performance



Stian Varre, CEO Nordpeis AS