DECLARATION OF PERFORMANCE

SalzMII+1-CPR-2020/06/08-GB



| PRODUCT Product type Type designation Product identification Intended area of use Fuel | Slow heat release appliance Salzburg M II + 1 See product instruction manual Heating of rooms in residential buildings Wood |
|---|--|
| MANUFACTURER Name Address | Nordpeis AS Gjellebekkstubben 11 3420 Lierskogen, Norway |
| CHECKS | |
| According to AVCP Standard Test institute | System 3 EN 15250:2007 Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625 has checked declared performance and issued test report no. RRF - 50 20 5549, RRF - 50 11 2822 |

DECLARED PERFORMANCE

| | | | | Harmonized |
|---|--------------------------|---------|---------------------|---------------|
| Essential Characteristic | Performance | | | technical |
| | | | | specification |
| Reaction to fire | A1 | | | |
| Minimum distances to combustible material | 50/150 | mm rear | | |
| | 100 mm side | | | |
| | other safety distances | | | |
| | according product manual | | | |
| Risk of falling embers | Approved | | | |
| Emission from combustion: | | | 2 | |
| Carbon monoxide at 13% O ₂ | CO = | 1125 | mg/m^3 | |
| Oxygen nitride NOx at 13% O ₂ | NOx = | 102 | mg/m^{3} | |
| Organic Gaseous Carbon at 13% O ₂ | OGC = | 62 | mg / m ³ | |
| Particulate Matter at 13 O ₂ | PM = | 36 | mg/m^3 | EN 15250:2007 |
| Surface temperatures | Approved | | | |
| Cleanability | Approved | | | |
| Mechanical durablity | Approved | | | |
| Releases of Hazardous Substances | Approved | | | |
| Total thermal output | | 40,2 | kWh | |
| Nominal output after elapsed time at 25% of max. mean temperature | P = | 2,7 | kW | |
| Flue gas temperature at nominal output | t _a = | 133 | °C | |
| Energy efficiency | η= | 85,3 | % | |

The udersigned is responsible for the manufacture and conformity with declared performance

Shanlane

Stian Varre, CEO Nordpeis AS