## **DECLARATION OF PERFORMANCE**

DavosALow-CPR-2020/08/04-GB



**PRODUCT** 

Product typeFireplace with steel insertType designationDavos A Low with N-29A

Product identificationSee serial number plate on productIntended area of useHeating of rooms in residential buildings

**Fuel** Wood

**MANUFACTURER** 

Name Nordpeis AS

Address Gjellebekkstubben 11 3420 Lierskogen, Norway

**CHECKS** 

According to AVCP System 3

**Standard** EN 13240:2001 /A2:2004 / AC:2007

**Test institute** Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625

has checked declared performance and issued test report no. RRF- NS 20 5571, RRF- 29 19 5299,

RRF- 40 20 5447

## **DECLARED PERFORMANCE**

Essential Characteristic	Performance			Harmonized technical specification
Reaction to fire	A1			
Minimum distances to combustible material	0	mm rear		
	0/210 mm side			
	other safety distances			
	according product manual			
Risk of falling embers	Approved			
Emission from combustion:				
Carbon monoxide at 13% O <sub>2</sub>	CO =	1000	$mg/m^3$	
Nitrogen oxides at 13% O <sub>2</sub>	NOx =	107	$mg/m^3$	EN 13240:2001 /
Organic gaseous compounds at 13% O <sub>2</sub>	OGC =	64	$mg/m^3$	A2:2004 / AC:2007
Particulate matter at 13% O <sub>2</sub>	PM =	26	mg / m <sup>3</sup>	
Surface temperatures	Approved			
Cleanability	Approved			
Mechanical durability	Approved			
Releases of Hazardous Substances	Approved			
Nominal output	P =	8,9	kW	
Flue gas temperature	t <sub>a</sub> =	269	°C	
Energy efficiency	η=	82,0	%	

The udersigned is responsible for the manufacture and conformity with declared performance

Stian Varre, CEO Nordpeis AS