DECLARATION OF PERFORMANCE

DavosPHigh-CPR-2020/07/08-GB



PRODUCT

Product typeFireplace with steel insertType designationDavos P High with N-29P

Product identificationSee serial number plate on productIntended area of useHeating of rooms in residential buildings

Fuel Wood

MANUFACTURER

Name Nordpeis AS

Address Gjellebekkstubben 11 3420 Lierskogen, Norway

CHECKS

According to AVCP System 3

Standard EN 13240:2001 /A2:2004 / AC:2007

Test institute Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625

has checked declared performance and issued test report no.RRF- 29 19 5396, RRF- 40 20 5512

DECLARED PERFORMANCE

Essential Characteristic	Performance			Harmonized technical specification
Reaction to fire	A1			
Minimum distances to combustible material	0	mm rear		
	1000	mm side		
	other safety distances			
acco		according product manual		
Risk of falling embers	Approved			
Emission from combustion:				
Carbon monoxide at 13% O ₂	CO =	875	mg/m^3	
Nitrogen oxides at 13% O ₂	NOx =	108	mg/m^3	EN 13240:2001 /
Organic gaseous compounds at 13% O ₂	OGC =	70	mg/m^3	A2:2004 / AC:2007
Particulate matter at 13% O ₂	PM =	28	mg / m ³	
Surface temperatures	Approved			
Cleanability	Approved			
Mechanical durability	Approved			
Releases of Hazardous Substances	Approved			
Nominal output	P =	10,5	kW	
Flue gas temperature	t _a =	286	°C	
Energy efficiency	η=	78,0	%	

The udersigned is responsible for the manufacture and conformity with declared performance

Stian Varre, CEO Nordpeis AS