

DECLARATION OF PERFORMANCE

N29A-CPR-2019/08/27-GB



PRODUCT

Product type Sheet Steel Insert
Type designation N-29A
Product identification See serial number plate on product
Intended area of use Heating of rooms in residential buildings
Fuel Wood

MANUFACTURER

Name Nordpeis AS
Address Gjellebekkstubben 11
3420 Lierskogen, Norway

CHECKS

According to AVCP System 3
Standard EN 13229:2001 /A2:2004 / AC:2007
Test institute Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625
has checked declared performance and issued
test report no. RRF - 29 19 5299, NS 20 5571

DECLARED PERFORMANCE

Essential Characteristic	Performance	Harmonized technical specification
Reaction to fire	A1	EN 13229:2001 /A2:2004 / AC:2007
Minimum distances to non-combustible material	90 mm rear 200/450 mm side other safety distances according product manual	
Risk of falling embers	Approved	
Emission from combustion: Carbon monoxide at 13% O ₂ Nitrogen oxides at 13% O ₂ Organic gaseous compounds at 13% O ₂ Particulate matter at 13% O ₂	CO = 1000 mg / m ³ NO _x = 107 mg / m ³ OGC = 64 mg / m ³ PM = 26 mg / m ³	
Surface temperatures	Approved	
Cleanability	Approved	
Mechanical durability	Approved	
Releases of Hazardous Substances	Approved	
Nominal output	P = 8,9 kW	
Flue gas temperature	t _a = 269 °C	
Energy efficiency	η = 82,0 %	

The undersigned is responsible for the manufacture and conformity with declared performance

Stian Varre, CEO Nordpeis AS