

# DECLARATION OF PERFORMANCE

SalzCConv-CPR-2015/09/30-GB

  
Nordpeis

## PRODUCT

<b>Product type</b>	Slow heat release appliance
<b>Type designation</b>	Salzburg C Convection
<b>Product identification</b>	See product instruction manual
<b>Intended area of use</b>	Heating of rooms in residential buildings
<b>Fuel</b>	Wood

## MANUFACTURER

<b>Name</b>	Nordpeis AS
<b>Address</b>	Gjellebekkstubben 11 3420 Lierskogen, Norway

## CHECKS

<b>According to AVCP Standard</b>	System 3 EN 15250:2007
<b>Test institute</b>	Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625 has checked declared performance and issued test report no. RRF- 50 15 3896

## DECLARED PERFORMANCE

Essential Characteristic	Performance	Harmonized technical specification
Reaction to fire	A1	EN 15250:2007
Minimum distances to combustible material	50 mm rear 50 mm side other safety distances according product manual	
Risk of falling embers	Approved	
Emission from combustion: Carbon monoxide at 13% O <sub>2</sub> Oxygen nitride NO <sub>x</sub> at 13% O <sub>2</sub> Organic Gaseous Carbon at 13% O <sub>2</sub> Particulate Matter at 13 O <sub>2</sub>	CO : < 1500 mg / m <sup>3</sup> NO <sub>x</sub> : < 200 mg / m <sup>3</sup> OGC : < 120 mg / m <sup>3</sup> PM : < 40 mg / m <sup>3</sup>	
Surface temperatures	Approved	
Cleanability	Approved	
Mechanical durability	Approved	
Releases of Hazardous Substances	Approved	
Total thermal output	54,5 kWh	
Nominal output after elapsed time at 25% of max. mean temp.	P = 3,6 kW	
Flue gas temperature at nominal output	t <sub>a</sub> = 140 °C	
Energy efficiency	η = 84 %	

The undersigned is responsible for the manufacture and conformity with declared performance



Stian Varre, CEO Nordpeis AS